

**IQMAX<sup>®</sup>**

# ***Model A***



## **CROSS FLOW AIR CURTAIN**



***Fresh Air Fresh Life!***

Optional:



Metal casing



Adjustable air  
deflector



High efficient  
motor



Quiet wind  
wheel



Remote  
control



Magnetic  
door



## CROSS FLOW AIR CURTAIN



**Warranty one year for product ,Warranty five years for motor**

- **Aesthetic arc panel design:** flow panel design, adopting hexagonal holes & rounded rectangle punching, larger air inlet and stronger panel rigidity.
- **Integrated air duct design:** the air outlet is stable, the air speed decays slowly, and the air curtain effect is more significant;
- **High-efficiency motor:** using independent R&D and self-produced motor, strong power, low noise and reliable performance;
- **Multi control modes:** adopt remote control and manual button mode, the operation is more convenient, standard 2-speed wind speed, can be 3 speeds for option, suitable for use in a variety of places;
- **Intelligent magnetic door switch (optional):** realize the humanized control of door opening and closing, greatly reduce the outflow of indoor air, and save more energy.

### Parameters

Voltage/Frequency : 220-240V/50Hz, or 110V/60Hz, 110V/50Hz, 220V/60Hz are all available.

| Model   | Diameter of Impeller (mm) | Input Power (W) | Air Velocity (m/s) | Air Volume (m³/h)/CFM | Noise (dB) | Net Weight (KG) | Gross Weight (KG) | Unit Size (mm) | Carton Size (mm) | Mounting Height (m) |
|---------|---------------------------|-----------------|--------------------|-----------------------|------------|-----------------|-------------------|----------------|------------------|---------------------|
| IM-CM09 | 120                       | 150             | 11.0               | 1780/1047             | ≤45        | 10.2            | 12.5              | 900×220×195    | 940×265×220      | 2.3-3               |
| IM-CM10 | 120                       | 150             | 11.0               | 1980/1164             | ≤46        | 12.3            | 13.8              | 1000×220×195   | 1040×265×220     | 2.3-3               |
| IM-CM12 | 120                       | 180             | 11.0               | 2370/1394             | ≤48        | 13.7            | 15.5              | 1200×220×195   | 1240×265×220     | 2.3-3               |
| IM-CM15 | 120                       | 250             | 11.0               | 2970/1747             | ≤49        | 16.3            | 18.5              | 1500×220×195   | 1540×265×220     | 2.3-3               |